

URAPACK-WB

KOLOUR KOAT™ TINT PACK FOR 6000 WB GLOSS URETHANE



Urapack-WB is a high solids, concentrated, water based tint system specially formulated for 6000 WB Gloss Urethane. Urapack-WB is formulated with high quality, ultra fine particle pigments that easily disperse in 6000 WB Gloss Urethane. Urapack-WB is a superior choice to obtain a solid colored finish in water based urethane.

Specifications / Compliances • Meets OTC, CARB, LADCO & SCAQMD VOC restrictions.



KEY FEATURES & TYPICAL BENEFITS

- 6 standard colors to choose from. (See *Kolour Koat™* color chart)
*Includes light gray, medium gray, buff, sun buff, black & white.
- Very economical way to achieve a durable, solid color urethane floor.
- Easily disperses into 6000 WB Gloss Urethane.
- Achieve a UV stable, chemical and wear resistant solid color floor with extremely low odor.

Typical Properties & Technical Information

PROPERTY	VALUE
Solids/Active Content, Percentage by weight	Concentrated
Pot Life	Refer to 6000 WB Urethane TDS
Dry Time - Tack Free	Refer to 6000 WB Urethane TDS
Dry Time - Foot Traffic	Refer to 6000 WB Urethane TDS
Dry Time - Heavy Traffic	Refer to 6000 WB Urethane TDS
Re-Coat Time Window	Refer to 6000 WB Urethane TDS
Application Temperature	50° F - 80° F
VOC (Volatile Organic Compound) Content	N/A
Appearance - Dry	Tinted and Medium/High Gloss

Information above is based on lab temperatures of 70° - 72°F at 50% RH. Using this product outside these conditions may affect the accuracy of the information above. Always test prior to use!

ALWAYS REFER TO SDS & READ FULL TECH DATA SHEET AND WARRANTY INFORMATION PRIOR TO USE.

RECOMMENDED APPLICATIONS

- Garages
- Basements
- High volume light traffic areas
- Many other concrete surfaces where an economical, solid color urethane is needed.



Surface Coatings, Inc.
134 Davis St. • Portland, TN 37148
P: (615) 323-9461 • F: (615) 323-9816
www.surfkoat.com | www.polyrezpro.com

SURFKOAT™
Surface Coatings, Inc.
Manufacturers of Industrial and Decorative Concrete Materials

APPLICATION INSTRUCTIONS

SURFACE PREP: Concrete surface must be clean and free of all contaminants and water. Do not apply if rain is forecast within 24 hours. If moisture is present or if the surface is not clean and free of all contaminants, the epoxy may have white spots and have premature delamination and failure.

Use Urapack-WB only in 6000 WB Gloss Urethane. Read 6000 WB Gloss Urethane technical data sheet for full surface prep and application instructions prior to use.

Substrate and air temperature must be no less than 40° F and not exceed 80° F. If applied outside these limits the coating may not achieve adequate film formation and may have excessive air entrapment, bubbles, blushing or hazing. Note that in direct sunlight, substrate temperature can exceed 150° F which can cause extreme bubbling issues.

Urapack-WB is available in Light Gray, Medium Gray, Buff, Sun Buff, Black and White only. See Kolour Koat chart for color selection.

MIXING: Mix entire container into two gallons of 6000 WB Gloss Urethane Part A for 1-2 minutes using a squirrel mixer prior to application. Only after the Part A and Urapack-WB are thoroughly blended should you mix Part A with Part B. (See 6000 WB Gloss Urethane tech data.) Allow any foam to settle prior to use. Material may separate during long term storage. Re-mix as needed.

USAGE RATE: Solid Opaque Finish: 32 ounces per 2.5 gallon kit 16 ounces per 1.25 gallon kit
*Usage rates are suggested amounts only! Due to varying sealer compositions, substrates, surface texture, porosity and desired look a test area is recommended to achieve desired results.

APPLICATION: Review the technical data and SDS for 6000 WB Gloss Urethane prior to use for surface prep instructions, application instructions, coverage rates and limitations.

FOR PERSONAL PROTECTION USE GLOVES, GOGGLES, AND RESPIRATORS.

CAUTION: Do not add too much color! Apply a test area prior to job application for desired appearance. Over pigmenting may cause color float or streaking, especially in the darker colors! Do not allow to puddle! The average usage is 1 quart (32 oz.) per 2.5 gallons of material for most opaque applications.

Check Urapack-WB for compatibility with competitors' water based urethane prior to use!

PLEASE NOTE: It is always recommended to test the product in a small, inconspicuous area (on the same concrete substrate) for desired results prior to application. Coverage rates may vary for all coatings and substrates depending on porosity, density, texture etc. When applying, do not exceed 400 sq. ft. per gallon. Applying too thin of a coating may cause inadequate film formation or performance expectations may be limited. **DO NOT USE ON BRICK.**

COF WARNING: OSHA and the American Disabilities Act (ADA) have now set enforceable standards for slip-resistance on pedestrian surfaces. The current coefficient of friction required by ADA is .6 on level surfaces and .8 on ramps. Surface Koatings, Inc. recommends the use of slip-resistant aggregate in all coatings or flooring systems that may be exposed to wet, oily or greasy conditions. It is the contractor and end users' responsibility to provide a flooring system that meets current safety standards. Surface Koatings, Inc. nor its sales agents will be responsible for injury incurred in a slip and fall accident. For interior floors subjected only to foot traffic, Cherry Surf-Wax may be used as an acceptable slip-resistant coating as it meets requirements for ASTM D2047.

PRECAUTIONS AND LIMITATIONS

- This product will freeze during storage. Store at temperatures above 40°F.
- All HVAC ventilation ducts should be somehow blocked prior to application so solvent fumes are not distributed.
- If using indoor, use proper ventilation while applying and for hours after application to ensure fumes are removed.
- It is not recommended to apply product over carpet, tile, or other types of floor adhesives.
- This product performs best when applied as one or two medium-light coats, not one heavy coat.
- Please be aware that this product when cured may be slippery when wet. An anti-slip additive, such as Surf-Grip, can be added to reduce slip hazards.
- This product is not resistant to brake fluid, gasoline, and many similar products.
- It is not recommended to thin product. Improper thinning may cause sealer to delaminate in a short time frame.
- This product may darken the surface of many new and existing concrete slabs. Test prior to use.
- Refer to 6000 WB Gloss Urethane tech data sheet for coverage, application and other information prior to use.

CLEAN-UP: Use soap and water. Dispose of containers in accordance with local, state and federal regulations.

PRODUCT REMOVAL: Refer to urethane technical data sheet.

SHELF LIFE: Up to one year from manufacture date in its original, unopened container stored at room temperature.

PACKAGING: Available in 1 quart containers.

Always read all technical information, label and SDS prior to use. This information can be found online or by calling customer service at the number below.

Surface Koatings, Inc. warrants our products to be of good quality, free of defects and will conform with our published specifications in force on the date of acceptance of the order. As the exclusive remedy for breach of this warranty, we will replace defective materials. Ninety days after Surface Koatings, Inc. has shipped the products, all our warranty and other duties with respect to the quality of the materials delivered shall conclusively be presumed to have been satisfied, all liability therefore terminates, and no action for breach of any said duties may thereafter be commenced. No warranty is expressed or implied as to the length of life of this product, or merchantability or fitness. Liability, if any, is limited to the purchase price of the material. Under no circumstances will Surface Koatings, Inc. be liable for a consequential damage to anyone in excess of the purchase price of the products.